

City of Costa Mesa Building Division POOL AND SPA REQUIREMENTS

The following information is required in a clear and legible manner. All information shall be complete and on the plans.

4 sets of plans showing all of the following with measurements shown from property lines, buildings, patio covers or other structures.

- 1. Name, address, phone number of owner.
- 2. Name, address, phone number, type of license of any contractors or subcontractors.
- 3. Pool and/or spa location.
- 4. Equipment location.
- 5. Gas and electrical meter locations.
- 6. Overhead service lines and serving pole location.
- 7. Type of gas and electrical conduits to be used.
- 8. Size of main electrical service (if less than 100 AMP, service is probably inadequate and will have to be upgraded to minimum City requirements.)
- 9. Rating (horsepower, voltage, amps) of all electrical equipment.
- 10. BTU rating of gas heater.
- 11. Distance and size of gas line.
- 12. All electrical outlets within 15 ft. of pool/spa.
- 13. Handrails, ladders, slides and diving boards (if any).
- 14. Location of doors and windows within 5 ft. of pool/spa.
- 15. The type of construction–gunite, poured concrete, prefabricated fiberglass or other.
- 16. The pool dimensions, including the depth and adequate cross-sections drawn to scale.
- 17. Computations, stress diagrams and other data sufficient to show the correctness of plans; including reinforcing steel schedule and details.
- 18. A statement by the applicant concerning the anticipated nature of the soil under and around the pool structure (expansive, moderately expansive, non-expansive). (A soils report may be required by Building Division prior to permit issuance.)
- 19. The Engineer's wet ink signature is required on pool structural plans and calculations.
- 20. All semi-private pools and spas shall conform to California Administrative Code Title 24 handicapped requirements (hotels, motels, recreation areas for lease to public or publicly funded projects and condominiums).
- 21. Where a permanently installed pool is constructed, at least one 120 volt receptacle shall be installed a minimum of 10 feet and not more than 20 feet from the inside wall of the pool and shall be protected by a ground fault circuit interrupter.
- 22. Indoor installation of spas and hot tubs, receptacles shall not be closer than five (5) feet to spa/tub.
- 23. Receptacles located within twenty (20) feet of a spa or hot tub shall be G.F.C.I.
- 24. Receptacles for spa/hot tub motors shall be G.F.C.I. protected.

GENERAL REQUIREMENTS

- 1. Pressure test shall be required on entire system (35 P.S.I air test or water fill) prior to back fill.
- 2. Overhead Edison drops shall be installed per NEC 680-8.
- 3. Clarification or additional information may be obtained by telephone: (714) 754-5273, between 8:00 a.m. and 4:30 p.m.

REQUIRED SETBBACKS

Pool Heater vent outlet as per (Chapter 8 CMC)

- 1. 4ft from doors/windows (CMC 802.2.6).
- 2. 4ft from attic vent. (CMC 802.8.2)

Pool/Spas:

Above-ground pools and spas shall not be located in the required front yard setback from a public street and are subject to 5 foot and 10 foot yard setbacks for main structures. Any deck that is raised higher than 6 inches above grade, will also be subject to the 5 foot and 10 foot yard setbacks requirements. Please consult with Planning Division regarding any in-ground pool and/or spa that are proposed to be located in the front yard.

- 1. Overhead Edison drops shall be installed per NEC 680-8 CEC.
- 2. It shall be unlawful for any person to install, remove, alter, repair or replace any plumbing, gas or drainage piping or any fixture, swimming pool heater or treating equipment in a building or premises without first obtaining a permit to such work from the Building Division.
- 3. Clarification or additional information may be obtained by telephone (714) 754-5273, between 8:00 am and 4:30 pm.